



2018 SUPER BUZZ RULES

ALUMINUM RACING SEAT AND 5 POINT HARNESS MANDATORY!!!!!!!

Car: 96-inch minimum wheelbase- Front and Rear tow loop mandatory- Must be considered as a compact car.

Engine:(Protest 250) 4 or 6 cylinders only and must be stock for make of car. No modifications or alterations to engine at all (no exceptions). Fuel injected only. No turbos, superchargers or rotary engines. Stock exhaust must extend past the driver's door. Cold air intake and aftermarket air filter allowed. Battery can be relocated for safety but must be in a battery box that is bolted down, covered and not exposed to the driver.

Transmission:(Protest 150) Auto or standard ok. Must be stock. NO MODIFICATIONS OR ALTERING!

Driveline:(Protest 100) Front wheel drive only. No AWD allowed rear end must be stock and in stock location for make of car. Up to 1-inch rear steer can be added if obtained by stock parts.

Suspension and Frame:(Protest 100) No altering in any way. Stock shocks, struts, racing springs ok right side only, moving suspension components must be in stock location unaltered.

Body:(Visual) 2 or 4 doors, all glass must be removed, back seat may be removed and any fire hazard substance, but all bracing must remain stock. (dash bracing, seat bracing, etc.). Aluminum fab dash with aftermarket gauges ok. Any openings from removing stock parts must have sheet metal covering to protect driver (back seat to trunk-firewall). Driver and passenger door can be minimum hulled for roll cage installation. All doors must be welded or bolted shut. No cutting on body anywhere. Car must have a 4-point roll cage that will be inspected and deemed safe before competing in the 2018 race season. If a car does not have a NAS inspection sticker you will not be allowed to race. THIS IS FOR YOUR SAFETY. Must have charged extinguisher in driver reach.

Wheels:(Visual) Max 8-inch racing wheel all 4 corners will be allowed. Stock steel wheels May be double centered and braced but stock. Oversize lug nuts are allowed and recommended all 4 corners. Aftermarket bead locks are ok RIGHT SIDE ONLY! NO ALUMINUM WHEELS WILL BE ALLOWED!!!

Tires:(Visual) Max tire size P235/70/17 highway DOT tire only. H500 or G60 pull offs. All 4 tires must be the same size (14,15,16 inch all 4 corners) Racing tires all 4 corners ok pull offs only (no new)

Brakes:(Visual) Must remain stock. 3-wheel brake configuration is allowed

Fuel cell may be used but installed safely in .020 metal or aluminum box, 1-inch straps and a barrier installed between driver.

Absolutely no working airbags and center of steering wheel must be padded if airbag removed.