

## 2021 JR MINI STOCK RULES

16 Years old and under only!!!!

3 cautions allowed per heat and feature

North Alabama Speedway will supply each driver a 6000 rpm chip for a MSD box at registration with our logo on it. It must be turned back in to the track for payout to be given.

If you have raced a previous season in any class you will not be allowed to race JR!!!!

This class is structured for kids to learn the race procedure and to be as safe as possible.

**Seat:** Must be full containment, must be sized for the driver with no filler material to take up space, and must have seatbelts with date code no older than 2 years old. Must have a NECK RESTRAINT SYSTEM that hooks properly to a racing helmet.

**Body:** Any RWD compact 4 cylinder car or truck. Must have stock firewall and floor pans and must extend to center of rear-end housing. Sheet metal body ok, no wedge bodies, must have mini stock style nose piece. One 8 inch spoiler on rear of car, must have tow hooks front and rear. Car will go through a track inspection to make sure it is safe before its allowed to be raced.

**Engine:** Must match make of car Ford to Ford Chevy to Chevy etc. Stock Block, Stock crankshaft, stock camshaft, stock clutch and flywheel no lightened flywheels must be stock weight. Stock intake no fuel injected intakes The only aftermarket performance part that can be under the hood is **1.** 350 cfm Holley style carb **2.** Header **3.** Plug wires **4.** Aluminum Radiator. **5.** Breather **6.** MSD Box that will accept a rev limiter chip. No digital MSD boxes. **7.** 1 inch carb spacer **8.** Fan and spacer

Head cannot be cut over .010, max bore .030, stock replacement piston only with no coatings, no race bearings of any kind, no race style rings, stock valves, no stainless or long valves allowed. No head studs

**Trans:** Stock Only

**Tires and Wheels:** 8 inch wheels and tires, racing tires ok

**Suspension:** any spring in stock location, weight jacks ok, front suspension must remain in stock location, after market shocks and struts ok non-adjustable, but must mount in stock location and bolt in stock holes with no adapters. Caster – Camber plates ok.

**Rear End:** Must be stock, can be locked or a locker installed

**Weight:** 1lb per cc, must be posted where tech man can see it

**Fuel:** Max 93 octane Gasoline only, no E85

**If you are caught trying to cheat in this class or bending rules you will automatically be moved to the Mini Stock class and banned from JR Mini Stock**